

XENON XP ACCESSORIES GUIDE



Honeywell

TABLE OF CONTENTS

- 1** Wall Mounts, Stands, Holders, and Covers
- 1** Charge and Communication Bases, Chargers, and Batteries
- 2** Cables and Power Supplies

WALL MOUNTS, STANDS, HOLDERS, AND COVERS



1950GSR-2-2-X
1950GHD-2-2-X
1950GSR-2USB-2-X
1950GHD-2USB-2-X

1950G Ratchet Stand
Provides a fixed stand for a corded scanner that enables presentation scanning and two-handed scanning.



50129064-001

Wall-Mount Cup
Holder Kit: Plastic bracket facilitates mounting of scanner to wall; two mounting screws included in kit.



STND-08R00-000-6

Rigid Presentation Stand - 3"
Stand: gray, 8 cm (3 in) height, rigid rod, large oval weighted base, cradle for Xenon™ 1900 and Xenon XP 1950 corded scanners.



STND-15R00-000-6

Rigid Presentation Stand - 6"
Stand: gray, 15 cm (6 in) height, rigid rod, large oval weighted base, Xenon cradle.

STND-22F00-001-6

Flexible Presentation Stand - 9"
Stand: gray, 22 cm (9 in) height, flexible rod, large oval weighted base, Xenon cup.



VISOR-190X-XT

Extended Sun Visor
Extended sun visor for use in direct sunlight or extremely bright environments. For use with Xenon XP 1950 corded and 1952 cordless scanners.



VISOR 190X

Sun Visor
Sun visor for use in direct sunlight or extremely bright environments. For use with Xenon XP 1950 corded and 1952 cordless scanners.



UCOVERXENON

Retractable Lanyard Cover
Fabric cover for hanging the scanner from a retractable lanyard.



VMHOLDERE-21029

Forklift Holder
Forklift/vehicle-mounted holder for holding a Xenon XP 1950 corded scanner between scans.

CHARGE AND COMMUNICATION BASES, CHARGERS, AND BATTERIES



BAT-SCN01A

Battery Pack
Battery: Lithium-ion battery for Xenon 1902 and Xenon XP 1952 cordless scanners.



BAT-SCN05

Smart Battery Pack
Battery: Lithium-ion battery for Xenon XP 1952 cordless scanners.



SUPCAP-SCN05

SuperCap Pack
Super Capacitor: Lithium-ion battery for Xenon XP 1952 cordless scanners.



MB4-BAT-SCN01NADO

4-Bay Battery Charger - Desk Mount
4-bay battery charger (NA) for use with Xenon 1902 and Xenon XP 1952 Lithium-ion batteries, NA desktop power supply (PS-050-4000D-NA), two mounting screws (100006897), and instructions (MBC-INST).



MB4-BAT-SCN01NAWO

4-Bay Battery Charger - Wall Mount
4-bay battery charger (NA) for use with Xenon 1902 and Xenon XP 1952 Lithium-ion batteries, NA wall-mount power supply (PS-050-4000W-NA), two mounting screws (100006897), and instructions (MBC-INST).

CCB10-010BT-07N	CCB11-010BT-07N	CCB12-010BT-HC	CCB13-010BT-07N	CCB15-010BT-HC
1952 Presentation CCB – Black (Battery)	1952 Presentation CCB – Lyric White (Battery)	1952 Presentation CCB – Healthcare (Battery)	1952 Desktop/Wall-Mount CCB – Black (Battery)	1952 Desktop/Wall-Mount CCB – Healthcare (Battery)
Xenon XP 1952 Presentation CCB, black, 10 m (32.8 ft), Bluetooth®.	Xenon XP 1952 Presentation CCB, white, 10 m (32.8 ft), Bluetooth.	Xenon XP 1952 Presentation CCB, healthcare white, healthcare software.	Xenon XP 1952 Horizontal CCB, black, 10 m (32.8 ft), Bluetooth.	Xenon XP 1952 Horizontal CCB, healthcare white, healthcare software.

CABLES AND POWER SUPPLIES

CBL-020-300-C00	CBL-120-300-C00	CBL-220-300-C00	CBL-420-300-C00	CBL-500-150-S00
RS-232 Power Cable	RS-232 Power Cable	RS-232 Power Cable	RS-232 Power Cable	USB Power Cable
Cable: RS-232 (5V signals), black, DB9 Female, 3 m (9.8 ft), coiled, 5V external power with option for host power on pin 9.	Cable: RS-232C (+/-12V signals), black, DB9 Female, 3 m (9.8 ft), coiled, 5V external power with option for host power on pin 9.	Cable: RS-232 (+5V signals), black, DB9 Male, 3 m (9.8 ft), coiled, external power with option for host power on pin 9 for connection to Wincor Beetle.	Cable: RS-232 (5V signals), Honeywell Bioptic Stratos™ Aux, black, 10 pin modular, 3 m (9.8 ft), coiled, host power possible (dependent upon scanner and Stratos models).	USB Type A HSM 5V 1.5 m (5 ft) straight cable.
CBL-500-300-S00	CBL-500-500-C00	CBL-503-300-C00	CBL-600-300-S00	CBL-600-400-C00
USB Power Cable	USB Power Cable	USB Power Cable	IBM Power Cable	IBM Power Cable
Cable: USB, black, Type A, 3 m (9.8 ft), straight, 5V host power.	Cable: USB, black, Type A, 5 m (16.4 ft), coiled, 5V host power.	Cable: USB, black, 12V locking, 3 m (9.8 ft), coiled, 5V host power.	Cable: IBM 46xx Port 9b, black, 3 m (9.8 ft), straight, 12V host power.	Cable: IBM 46xx Port 9b, 12V power, coiled, 4 m (13.1 ft).
CBL-720-300-C00	CBL-MAG-300-S00	46-00525	46-00526	46-00528
Keyboard Wedge Power Cable	RS-232 Power Cable	Power Supply – NA Plug	Power Supply – EU Plug	Power Supply – AU Plug
Cable: KBW, black, PS2, 3 m (9.8 ft), coiled, 5V external power with option for host power.	Cable: RS-232 (5V signals), Magellan Aux Port, black, 10 pin modular, 3 m (9.8 ft), straight, external power with option for host scanner power.	Power Supply: NA plug, 1.0A @ 5.2V DC, 90–255V AC @ 50–60 Hz.	Power Supply: EU plug, 1.0A @ 5.2V DC, 90–255V AC @ 50–60 Hz.	Power Supply: AU plug, 1.0A @ 5.2V DC, 90–255V AC @ 50–60 Hz.
46-00529				
Power Supply – CN Plug				
Power Supply: CN plug, 1.0A @ 5.2V DC, 90–255V AC @ 50–60 Hz.				

Honeywell Safety and Productivity Solutions
 9680 Old Baites Road
 Fort Mill, SC 29707
 800-582-4263
www.honeywell.com